

XTRABOND®100

PREMIUM SILICONIZED ACRYLIC SEALANT



XtraBond®100 is Premier's most advanced siliconized acrylic sealant. The product has been formulated to provide a mildew resistant, super-tight bond for demanding applications.

XtraBond®100 is the product of choice when installing windows & doors to ensure long-lasting results. Installers prefer the product for its quick cure. Its unique chemistry offers the best balance of rugged durability with simple, quick clean-up.

FEATURES

- Cleans Up with Water
- Excellent Flexibility
- Mildew Resistant
- Quick Curing
- Paintable

APPLICATIONS

- General Construction
- Window & Door
- Kitchen & Bath

Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green



Who is Premier?

XtraBond®100 is a product distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.

For orders or more information contact:

Caliber Supply, LLC

P.O. Box 22041 Mesa, AZ 85277

Phone (480) 336-8342

Caliber-Supply.com



XTRABOND[®]100

PREMIUM SILICONIZED ACRYLIC SEALANT



PROPERTIES:

Skin Time	Internal Method	< 30 minutes @ 70°F / 50% RH
Tack Free Time	Internal Method	< 60 minutes @ 70°F / 50% RH
Cure Rate	Internal Method	1/4" Bead in 72 Hours
VOC	EPA Method 24	< 30 g/L, less water and exempt solvents
Elongation @ Break	ASTM D412	250 - 350%
100% Modulus of Elasticity	ASTM D412	75 - 125 psi
Shore A	ASTM C661	25 ± 5
Tensile Strength	ASTM D412	100 - 150 psi
Staining	ASTM D2203	None
Sag/Slump	ASTM D2202	Minimal; < 0.2"

SPECIFICATIONS: XtraBond[®]100 meets the requirements of ASTM C834 Grade -18°C, Type OP.

COLORS: White.

DIRECTIONS: For best results, prepare a clean surface. Cut nozzle to desired bead size. Apply with caulking gun, forcing sealant onto the substrate, then tool if needed. Clean excess material with water.

STORAGE: Material is to be stored under controlled dry environment (below 75° F). Use within 12 months from date of manufacture. Pails/Drums; use within 6 months from date of manufacture. For best results, keep material in tightly closed containers when not in use. Do not freeze.

SURFACE PREPARATIONS: The substrate must be clean, dry, frost free, sound and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

LIMITED LIFETIME WARRANTY: This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

PACKAGING



CARTRIDGES



SQUEEZE TUBES



PAILS



DRUMS