

XTRABOND[®]150

RTV SILICONE SEALANT



XtraBond[®]150 is a one component, permanently flexible, RTV (Room Temperature Vulcanizing) mildew-resistant silicone sealant that is the industry standard. The product's tough chemical resistance makes it a worry-free solution for a wide range of applications.

XtraBond[®]150 provide excellent adhesion to tile, glass, vinyl, aluminum, and sheet metal. The product is engineered to cure rapidly when exposed to atmospheric moisture, to form a durable tight bond that contractors and installers count on. A wide range of packaging options provides users with total flexibility in how the product is applied.

FEATURES

- Excellent Adhesion to Glass
- Window & Door Approved
- Easy to Gun, Easy to Tool
- Non-Sag & Slump
- Non-Paintable

APPLICATIONS

- General Construction
- Kitchen & Bath
- Transportation
- Industrial

Green Advantage Program

This XtraBond[®] product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green



Weather Defense System

This XtraBond[®] product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



Who is Premier?

This XtraBond[®] product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.

For orders or more information contact:

Caliber Supply, LLC

P.O. Box 22041 Mesa, AZ 85277

Phone (480) 336-8342

Caliber-Supply.com



XTRABOND[®]150

RTV SILICONE SEALANT



PROPERTIES:

Skin Time	Internal Method	< 15 minutes @ 70°F / 50% RH
Tack Free Time	Internal Method	< 45 minutes @ 70°F / 50% RH
Cure Rate	Internal Method	1/4" Bead in 48 Hours
VOC	EPA Method 24	< 30 g/L, less water and exempt solvents
Elongation @ Break	ASTM D412	350 - 400%
100% Modulus of Elasticity	ASTM D412	40 - 80 psi
Shore A	ASTM C661	20 ± 5
Tensile Strength	ASTM D412	160 - 200 psi
Sag/Slump	ASTM D2202	Minimal; < 0.2"
UV Rating	ASTM G154	No discoloration or change in appearance after 5000 hours
Service Temperature	Internal Method	-40 - 300°F

COLORS: This product is offered in a wide variety of colors using our Custom Color Matching & Mixing System. For current color offerings, please visit our website: www.premierbuildingsolutions.net/color.

SURFACE PREPARATIONS: The substrate must be clean, frost free and free of any oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if surface is contaminated. It is recommended to test all substrates prior to applications.

DIRECTIONS: For best results, prepare a clean surface. Cut nozzle to desired bead size. Apply with caulking gun, forcing sealant onto the substrate, then tool if needed. Clean excess material with mineral spirits or similar solvent.

STORAGE: Material is to be stored under controlled dry environment (below 75° F). Use within 18 months from date of manufacture. Pails/Drums; use within 12 months from date of manufacture. For best results, keep material in tightly closed containers when not in use.

PACKAGING



CARTRIDGES



PAILS



DRUMS

LIMITED LIFETIME WARRANTY: This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.