

XTRAFOAM™MB

MULTI-BOND ADHESIVE FOAM



XtraFoam™MB is multi-purpose, one component, industrial grade foam product. The product is ideal for subfloor, marble, drywall, insulation panel and metal applications where a high bonding strength is required. Its unique chemistry ensures extremely low post-expansion, while adhering well to all building materials such as wood, concrete, brick, marble, granite – even when applied in cold temperatures.

XtraFoam™MB is the product of choice for professionals who need a product that can deliver highly durable adhesion, thus minimizing the need for nails or screws.

USES:

XtraFoam™MB can be used for a variety of applications including, but not limited to, fixing & sealing building materials, countertop applications, fastener applications, subfloor, drywall, panels.

DIRECTIONS FOR USE:

Type: ALL substrates except PE and PP. State of Surface: clean, free of dust and grease. Preparation: Moistening of the surfaces improves adhesion, curing, and denser cellular structure. Follow directions on attaching Foam Gun Applicator. For excellent adhesion, do not allow more than 8 minutes to elapse between applying adhesive and attaching substrate. Longer than eight minutes 'open time' will negatively affect adhesion. After following instructions for set-up, the dispensing gun is ready to use. For best results, use in temperatures between 60-100°F. For better results, spray mist into cavity prior to applying foam.

STORAGE:

Material must be stored upright when not in use. 12 months in unopened packaging in a cool and dry storage place at temperatures of 75°F.

HEALTH AND SAFETY RECOMMENDATION:

Apply the standard industrial hygiene techniques. Wear gloves and safety goggles. Remove cured foam by mechanical means only, never burn away. SEE INDIVIDUAL CANS OF FOAM FOR SPECIFIC INSTRUCTIONS.

FEATURES:

- Excellent Adhesion to Various Substrates
- For Professional Gun Applications
- Cold Temperature Application
- Low Expansion Formula
- Low Post Expansion
- Excellent Stability
- High Bond



For orders or more information contact:

Caliber Supply, LLC

P.O. Box 22041 Mesa, AZ 85277

Phone (480) 336-8342

Caliber-Supply.com



CHEMICAL & PHYSICAL PROPERTIES

Base	Polyurethane
Curing System	Moisture Cure
Core Density	1.25 -1.70 lbs./ cu.ft.
R-Value ASTM C518	4.25 per inch
Pressure Build	0.15-1.20 psi
Color	Yellow
Service Temp	230°F
Curing Rate	30 Minutes for a ½ bead
Take Free	8-10 minutes for a ½ bead
Shelf Life	12 months, from date of mfg.
Coverage	219 linear feet

Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.

Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly and VOC compliant products. Learn more at www.PremierBuildingSolutions.net/green

Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



PACKAGING



AEROSOL CANS

LIMITED LIFETIME WARRANTY:

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

211024-PBS-XtraFoamMB-Ver2