

# XTRAFASH™

## WATER & MOISTURE BARRIER SYSTEM

XtraFlash™ Nail-On Flashing is a heavy duty, flexible, tear resistant, woven polypropylene flashing designed to prevent air and water intrusion when used around windows and doors. The nail-on product is engineered to provide excellent durability – even when exposed to high winds or prolonged ultraviolet rays.

XtraFlash™ Nail-On complies with all ASTM E-2112-07 & AAMA 2400 -02 installation requirements. The product's cross-woven design delivers a balance of strength and flexibility that makes it a favorite of installation professionals. The product is mechanically fastened with staples or capped nails.

### FEATURES

- Excellent Moisture Resistance - Up to 140 Hrs at 100% Humidity
- Totally Compatible with Premier Sealants
- Resists Cracking or Shrinkage
- Superb Wind & Tear Resistant
- UV Resistant Up to 6 months
- Mold & Mildew Resistant

### APPLICATIONS

- Perimeter Sealing of All Exterior Wall Penetrations
- Perimeter Sealing of Windows & Doors

#### Green Advantage Program

This XtraBond® product is a part of Premier's "Green Advantage" Program – the designation of our commitment to not only superior products & services, but also the environment. Our engineering formulations, manufacturing standards and production practices allow us to be a leader in the supply of eco-friendly & VOC compliant products. Learn more at [www.PremierBuildingSolutions.net/green](http://www.PremierBuildingSolutions.net/green)



#### Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



#### Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



**For orders or more information contact:**

**Caliber Supply, LLC**

**P.O. Box 22041 Mesa, AZ 85277**

**Phone (480) 336-8342**

**Caliber-Supply.com**





# XTRAFLASH™

## WATER & MOISTURE BARRIER SYSTEM

### PROPERTIES:

Thickness .....	13 mil (ASTM D882)
Water Vapor Permeance .....	<.02 perms (ASTM F1249)
Water Vapor Resistance .....	140 hours
Mold & Fungal Growth .....	NONE (ASTM G21)
Accelerated UV .....	>0.95% strength after 2000 hrs
Tensile Strength - Warp .....	181 (ASTM D751)
Grab Tensile Strength-Weft .....	148 (ASTM D2261)
Tongue Tear - Warp .....	48 (ASTM D2261)
Tongue Tear- Weft .....	34 (ASTM D2261)
Mullen Burst .....	240psi (ASTM D3786)
Low Temp Bend .....	Passes

**COMPATIBILITY:** XtraFlash™ has been tested with all the XtraBond® Sealants and has been determined compatible. If this product is used with any other sealants, a compatibility test and adhesion test must be conducted by the purchaser or end user. The purchaser should contact the company providing such products.

**LIMITATIONS:** XtraFlash™ should not be installed horizontally or at slopes less than 60 degrees. XtraFlash™ should be covered in a reasonable amount of time after installed around the window or door perimeter. It is not recommend for use on roofs or skylights. Please inspect the Flashing prior to covering to ensure product is free of defect from protrusions or damage that may compromise the integrity of the product's moisture resistance.

**NOTICE:** Splicing in the weave of the product is a normal occurrence during the manufacturing process in order to achieve continuous 300 foot roll lengths. Do not use or apply this spliced section; simply cut off the spliced section, discard, and continue with normal application.

**HOW TO USE:** Please refer to installation instructions. Contact your local rep or visit [www.premierbuildingsolutions.net](http://www.premierbuildingsolutions.net)

**MSDS:** Please refer to the SDS for details. Contact your local rep or visit our website at [www.premierbuildingsolutions.net](http://www.premierbuildingsolutions.net)

**LIMITED LIFETIME WARRANTY:** This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

*Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.*

### PACKAGING



ROLLS