

NEXO[®] LIQUI-FLASH

FLUID APPLIED MEMBRANE

INDUSTRIAL • CONSTRUCTION • WINDOW & DOOR • SIDING • ROOFING

TECHNICAL DATA SHEET

NEXO[®] LIQUI-FLASH is a high performance, moisture curing liquid applied flashing and sealant designed to ensure a clean and easy application over horizontal and vertical surfaces. The low VOC, non sag formula has been designed to deliver tenacious adhesion to the most common construction substrates.

NEXO[®] LIQUI-FLASH is used for a variety of applications including fluid applied flashing, expansion joints, precast concrete panel joints, window and door perimeters, aluminum, masonry and vinyl siding.

FEATURES

- ✓ Durable, Flexible Bond
- ✓ Won't Shrink or Stain
- ✓ For Interior & Exterior
- ✓ Low VOCs
- ✓ Aggressive Adhesion
- ✓ Color: Gray
- ✓ No Solvents
- ✓ Paintable in 2 Hours
- ✓ Complies AAMA 714-15
- ✓ Vertical & Horizontal Surfaces
- ✓ Can be applied in a wide range of temperature & weather (-40°F - 140°F)

DIRECTIONS FOR USE

Read and understand technical data sheet completely before beginning installation. Always do a test area to ensure product satisfaction and to become familiar with proper application techniques.

Surface Preparation: The surface must be clean and free of any frost, oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if surface is contaminated. It is recommended to test all substrates prior to application.

Application: Apply by spreading it to a 12-15 mil thickness (opaque coverage) with a brush or tool, ensuring it extends 4-6 inches wide. It cures into a waterproof, airtight rubber membrane that can be applied to sheathing, concrete, and framing.

Curing: Liquid flashing generally skins over within 30 to 60 minutes and fully cures in 2 to 6 hours (70°F, 50% RH). It is a moisture-cure product, meaning it will cure faster in high humidity/warm weather and slower in cold, dry conditions.

Storage/Shelf Life: Material is to be stored under a controlled and dry environment (below 75° F). Use within 10 months from date of manufacture. For best results, keep material in tightly closed containers when not in use. Do not freeze.

 **EcoFRIENDLY + VOC COMPLIANT**



Caliber Supply, LLC
Phone (480) 336-8342
Fax (480) 269-9170

P.O. Box 22041
Mesa, AZ 85277
Caliber-Supply.com