

# NEXO FLASH®

## NAIL-ON FLASHING

### TECHNICAL DATA SHEET

**NEXO FLASH®** nail on flashing is a heavy duty, flexible, tear resistant, woven polypropylene flashing designed to prevent air and water intrusion when used around windows and doors. The nail-on product is engineered to provide excellent durability – even when exposed to high winds or prolonged ultraviolet rays.

**NEXO FLASH®** complies with all ASTM E-2112-07 & AAMA 2400-02 installation requirements. The product's cross-woven design delivers a balance of strength and flexibility that makes it a favorite of installation professionals. It is mechanically fastened with staples or capped nails.

**NEXO FLASH®** is engineered for many applications, including perimeter sealing of windows & doors and perimeter sealing of all exterior wall penetrations.

### FEATURES

- ✓ Available in 9" x 300' rolls
- ✓ ASTM E2112-07 & 2400-02 Approved for Exterior Window & Door Installation
- ✓ Excellent Moisture Resistance: Up to 140 Hrs at 100% Humidity
- ✓ Superb Wind & Tear Resistant
- ✓ UV Resistant Up to 6 months
- ✓ Fast & Flexible Installation
- ✓ Mold & Mildew Resistant
- ✓ Resists Cracking or Shrinkage

### DIRECTIONS FOR USE

**COMPATIBILITY:** Nexo Flash® has been tested with all the Nexo Flex® Sealants and has been determined compatible. If this product is used with any other sealants, a compatibility test and adhesion test must be conducted by the purchaser or end user. The purchaser should contact the company providing such products.

**LIMITATIONS:** Nexo Flash® should not be installed horizontally or at slopes less than 60 degrees. Nexo Flash® should be covered in a reasonable amount of time after installed around the window or door perimeter. It is not recommend for use on roofs or skylights. Please inspect the flashing prior to covering to ensure product is free of defect from protrusions or damage that may compromise the integrity of the product's moisture resistance.

**NOTICE:** Splicing in the weave of the product is a normal occurrence during the manufacturing process in order to achieve continuous 300 foot roll lengths. Do not use or apply this spliced section; simply cut off the spliced section, discard, and continue with normal application.

 **EcoFRIENDLY + VOC COMPLIANT**

© 2017-2026 Caliber Supply, LLC



Caliber Supply, LLC  
Phone (480) 336-8342  
Fax (480) 269-9170

P.O. Box 22041  
Mesa, AZ 85277  
Caliber-Supply.com

# NEXO FLASH<sup>®</sup>

## NAIL-ON FLASHING

### TECHNICAL DATA SHEET [PAGE 2]

#### CHEMICAL & PHYSICAL PROPERTIES

Thickness	13 mil (ASTM D882)
Water Vapor Permeance	<.02 perms (ASTM F1249)
Water Vapor Resistance	140 hours
Mold & Fungal Growth	NONE (ASTM G21)
Accelerated UV	>0.95% strength after 2000 hrs
Tensile Strength Warp	181 (ASTM D751)
Grab Tensile Strength-Weft	148 (ASTM D2261)
Tongue Tear - Warp	48 (ASTM D2261)
Tongue Tear- Weft	34 (ASTM D2261)
Mullen Burst	240psi (ASTM D3786)
Low Temp Bend	Passes

#### LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Caliber Supply, LLC (Caliber) is limited to a full refund of the purchase price or product replacement if product is proven defective. Caliber shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose. Caliber Supply specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

© 2017-2026 Caliber Supply, LLC



Caliber Supply, LLC  
Phone (480) 336-8342  
Fax (480) 269-9170

P.O. Box 22041  
Mesa, AZ 85277  
Caliber-Supply.com